## Video/Surveillance V300 Video Streaming Hard Drive

### Stream. Record. Edit.



3	2	1	500
тв	тв	тв	GB

Color

Toshiba's 3.5-inch V300 Video Streaming Hard Drive with up to 3 TB lets you stream, record, edit and play video content on DVR, TV or NVR – with all the efficiency and reliability you need. A 64 MB buffer helps deliver smooth performance, while temperature control technology limits heat buildup, extending service life for added reliability. A drive that's quiet and more efficient than ever, thanks to Toshiba's Silent Seek Technology, and reduced energy consumption.

#### Use for:

- Video Editing Systems
- Set-Top-Box (STB)
- Digital Video Recorders (DVR)
- Network Video Recorders (NVR)
- Video Surveillance Systems



#### SATA 3.5" SATA Hard Drive

- 64 MB buffer
- 24/7 24/7 operation
- 😴 Up to 16 cameras
- Toshiba Silent Seek Technology
- Temperature control

## Manual

Toshiba\_Installation\_and\_Safety.pdf 🛃


### **Tools**

ToshibaStorageDiagnosticTool\_1.30.8920.zip 🛃





## **Product Specifications**



### **Basic Specifications**

Form factor	3.5-inch	
Interface	6.0 Gbit/s	
Number of cameras supported	16	
Drive bays supported	1 to 8	
Advanced Format (AF)	Yes	
RoHS compatible	Yes	
Halogen Free	Yes	
Shock Sensor	Yes	
Performance		
Rotational speed	5940 rpm (3 TB),	

### **Box Content**

Box Content	3.5-inch internal hard drive - V300 Video Streaming Hard Drive	
Physical		
Weight (approx.)	680 g max. (2 TB, 3 TB), 450 g max. (500 GB, 1 TB)	
Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm	
Environmental		
Acoustics (idle mode)	24 dB typ. (3 TB), 22 dB typ. (2 TB), 19 dB typ. (500 GB - 1 TB)	
Shock (non-operating)	300 G / 2 ms	
Shock (operating)	70 G / 2 ms duration	
Vibration (non-operating)	1.04 G (2 to 200Hz)	
Vibration (operating)	0.67 G (5 to 500 Hz)	
Temperature (operating / non-operating)	0 to 65° C / -40 to 70°C	

#### **Power Management**

Consumption - Active Idle	4.20 W typ. (3 TB),	
	3.30 W typ. (2 TB),	
	3.00 W typ. (500 GB, 1 TB)	

### **Power Management**

Supply voltage

Native Command Queing

Unrecoverable error rate

Buffer size

Reliability

24/7 operation

Load / Unload Cycle

Workloads

(NCQ)

5VDC (±5%) / 12VDC (±10%)

5700 rpm (500 GB - 2 TB)

64 MB

supported

72 TB/year

Yes

300,000

1 per 10E14 bits read

## **Product Range**

Part number	Capacity	Color
HDWU130UZSVA (Bulk)	3 TB	-
HDWU120UZSVA (Bulk)	2 TB	-
HDWU110UZSVA (Bulk)	1 TB	-
HDWU105UZSVA (Bulk)	500 GB	-

# Logistical Information:

Box dimensions
Box weight (gross)
Master carton dimensions
Master carton weight (gross)
Boxes per master carton
Pallet dimensions
Pallet weight (net)
Units per pallet

n/A n/A 321 x 406 x 213 mm 16 kg (typ.), 11 kg (typ.) (1TB, 500GB) 20 n/A n/A 720

## Contact

Toshiba Electronics Europe GmbH

Hansaallee 181 40549 Düsseldorf Germany